

71164 U.S. PTO

08/859378



05/20/97

UNITED STATES PATENT APPLICATION

of

H. BRITTON SANDERFORD

ROBERT E. ROUQUETTE

~~and~~

~~JAMES D. ARTHUR~~

for

WIRELESS ALARM SYSTEM

0859378 052097

a
a

08559375-052097

5

BACKGROUND OF THE INVENTION

This invention relates to a wireless warning system for use in a large office building, and more particularly a wireless fire warning and detection system which employs spread spectrum technology with high reliability for continuously monitoring the building.

Insal

DESCRIPTION OF THE PRIOR ART

0

A number of systems and techniques have been employed in the prior art as a warning system for large buildings. These include having warning sensors for detecting fire, security, or other means wired directly to a main console, with indicators that a particular sensor has been activated. Systems also have been developed employing a radio link between the sensor and receiver. For example, U.S. Patent No. 4,550,312 to Galloway et al. teaches the use of wideband sensors and transmitters. The sensors/transmitters transmit digital information to a central station by radio. These transmissions of messages are proceeded by an additional access code to identify a particular property. This increases the message overhead, however, which lowers system throughput and lowers battery life.

5

0

U.S. Patent No. 4,661,804 to Abel discloses a receiver-decoder used with a plurality of encode or transmitter

units using digitally encoded addresses. This use of multiple redundant 35 second interval short transmissions is used to achieve reliable throughput.

U.S. Patent No. 4,734,680 to Gehman et al. teaches the use of a pseudorandom number to lower probability of repeat data collisions. The Gehman invention provides for only four bits or sixteen time slot positions over which to transmit, which are inadequate for large systems with hundreds of transmitters. The Gehman disclosure does not teach the use of a randomization interval with hundreds of possible of time slots with spread spectrum so that a destructive data collision can only occur in one chip time. Further, the Gehman patent does not teach the use of the transmitters unique address as a seed to the pseudorandom number generator, preventing two transmitters from drifting into lockstep transmitting schedule.

OBJECTS AND SUMMARY OF THE INVENTION

An object of the present invention is to provide a wireless warning system having a high reliability for transmitting digital data via radio waves from an alarm or data transmission device to a remotely located receiver.

Another object of the invention is to provide a wireless warning system capable of data error detection and error correction using redundancy, for increasing communications

reliability.

A further object of the invention is to provide a wireless warning system having a safety margin against jamming and undesirable interference.

According to the present invention, as embodied and broadly described herein, a wireless warning system is provided comprising a plurality of sensors coupled to a plurality of spread spectrum transmitters, respectively. The plurality of sensors are for detecting or warning against smoke, heat, unauthorized entry, or other sensing device to indicate some particular function in a room of a building. The system further includes at least one spread spectrum receiver having polar diversity antennas and microprocessor having a display, with the microprocessor coupled to the spread spectrum receivers.

An apparatus coupled to a modulation input of an oscillator of a spread spectrum transmitter is provided for controlling the spread spectrum transmitter, which includes chip-code-generation means, preamble means, address means, and data means. The chip-code-generation means can be embodied as a recirculating register, the preamble means can be embodied as a preamble register, the address means can be embodied as an address register, and the data means can be embodied as a data register. The recirculating register is coupled to the modulation input of the oscillator for storing the spread spectrum code. The

recirculating register also outputs the spread spectrum chip code as a modulating voltage to the modulation input of the oscillator. The preamble register is coupled to the modulation input of the voltage controlled oscillator. The preamble register stores a preamble, and outputs, during a transmitting interval, the preamble as a modulating voltage to the modulation input of the voltage controlled oscillator. The preamble may include a coarse lock preamble and a fine lock preamble.

The address register is coupled to the modulation input of the voltage controlled oscillator through the preamble register. The address register stores a device address and a type code, and outputs, during a transmitting interval, the device address and the type code as a modulating voltage to the modulation input of the voltage controlled oscillator.

The data register is coupled to the data input and to the modulation input of the voltage controlled oscillator through the preamble register and the address register. The data register stores data received from the data input, and outputs, during the transmitting interval, the data as a modulating voltage to the modulation input of the voltage controlled oscillator.

The present invention further includes ^{an} error detection means coupled to the data register for putting a redundancy check code word at the end of a data sequence, for error detection.

A timing circuit is provided coupled to the enable input of

5 0055376 "552097
10
15
20
The present invention further includes an apparatus for synchronizing spread spectrum chip code using a two step algorithm in a process coupled to a receiver having a quieting output. The apparatus includes means for correlating a first signal from the quieting output of the receiver with ~~one chip~~ ^{multiple code iterations} of the spread spectrum chip code by comparing the first signal to an adaptive average ^{to be exceeded by A PR} by a preset margin. The means for correlating includes determining whether the amplitude of the first signal exceeds the preset margin. Included are means coupled to the correlating means for computing the adaptive average, in response to the first signal not exceeding the preset margin. The computing means adds the amplitude of the first signal to the previously computed adaptive average. Means coupled to the quieting output of the receiver is provided for correlating a second signal in response to the first signal exceeding the preset margin. The second signal is correlated with a portion ^{multiple code iterations A PR} of the time duration of ~~one chip~~ of the spread spectrum signal. The means for correlating the second signal compares the amplitude of the second signal to an adaptive average by a preset margin to determine whether the second signal exceeds the preset margin.

A second species of the spread spectrum chip code synchronization method and apparatus, according to the present invention, is provided. The second species includes the spread spectrum chip code synchronization apparatus coupled to a

baseband output of a receiver. The apparatus includes means coupled to the baseband output of the receiver for sampling and digitizing a plurality of analog signals from the baseband output of the receiver, for generating a plurality of data signals. Each of the analog baseband signals is sampled and digitized during one chip time. Register means are provided, coupled to the sampling and digitizing means, for shifting the plurality of data signals sequentially through a plurality of shift registers. Means is provided coupled to the register means for adding in parallel each of the plurality of data signals stored in the plurality of registers according to a plurality of predetermined weights for each of the plurality of data signals. The adding means generates a correlation sum.

Comparing means coupled to the adding means compares the correlation sum to a preset margin. Means coupled to the comparing means dithers a chip clock by at least one portion of one chip time, thereby improving clock lock.

A third species of the spread spectrum chip code synchronization apparatus is provided according to the present invention. The apparatus comprises means coupled to the baseband output of the receiver for sampling and digitizing a plurality of analog signals from the baseband output of the receiver. The sampling and digitizing means also generates a plurality of data signals. Each of the analog signals is sampled and digitized

00559375 052097

during one chip time.

Register means also is provided in the third species of the spread spectrum chip code synchronization apparatus, according to the present invention, coupled to the sampling and digitizing means for shifting and recirculating the plurality of data signals sequentially through a plurality of shift registers. Means additionally is provided coupled to the register means for adding sequentially the data signals passing through one of the shift registers according to a predetermined weighting algorithm.

Additional objects and advantages of the inventions will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate a preferred embodiment of the invention, and together with the description, serve to explain the principles of the invention.

Fig. 1 is a block diagrammatic view of the wireless sensor and detector system according to the present invention;

Fig. 2 is a schematic diagram of a spread spectrum transmitter;

Fig. 3A is a block diagram of a spread spectrum receiver;

Fig. 3B is a schematic diagram of a spread spectrum chip code microprocessor of the receiver;

Fig. 4 is a flow chart of the code locking algorithm;

Fig. 5 is a timing diagram of the spread spectrum chip positions;

Fig. 6 is a schematic diagram of a parallel correlator coarse lock dither circuit for proving a fine lock; and

Fig. 7 is a schematic diagram of a parallel correlator with a serial correlation sum accumulation.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings.

Wireless Warning Detection System

Fig. 1 illustrates the wireless warning system of the present invention. A plurality of sensors S1, S2, . . . , SN, are coupled to a plurality of spread spectrum transmitters X1, X2, . . . , XN, respectively. Also shown are the elements of a base station including a first spread spectrum receiver 502 and a second spread spectrum receiver 504, each of which are coupled to polar diversity antennas 507, 509, respectively. A microprocessor 506 having a microprocessor display is coupled to

the first spread spectrum receiver 502 and the second spread spectrum receiver 504. The wireless warning detection system of Fig. 1 provides a high reliability for transmitting digital data via radio waves from a sensor S1, S2, . . . , SN. The sensor S1, S2, . . . , SN may be, for example, a smoke head detector, a security sensing device, or other initiating device or modulating device. As set forth below, the high reliability of the system includes means for data error detection and error correction.

The preferred embodiment consists of many sensor devices S1, S2, . . . , SN which may be a smoke detector, pull station, contact alarm, waterflow detector, guard station, or security access controller. These can be expanded directly to include voice modulation, local area network data link, long-range alarm monitoring, remote power meter reading, remote process control, etc.

The initiating device provides either a contact input or reflected light smoke chamber level or data byte to the spread spectrum transmitters X1, X2, . . . , XN. The spread spectrum transmitters X1, X2, . . . , XN include means for data message encoding in serial form and data integrity validation, means for re-sending the message to achieve redundancy, means for randomizing the message transmit interval to avoid repeat collisions, means for modulating the serial message into spread spectrum form and means for transmitting the spread spectrum

carrier at the desired frequency.

5 The spread spectrum receiver's antennas 507, 509 minimize
signal fading via polar diversity. Using two receivers provides
redundancy as a primary and secondary means for receiving
transmissions. The two polar diversity antennas provide spatial
diversity against signal fading. The spread spectrum receiver
10 507, 509 collects the RF energy from polar diversity antenna 507,
509 and filters out undesirable frequencies. The receivers
compare and synchronize desirable frequencies to the spread
spectrum code of interest thereby extracting the original serial
transmission. The spread spectrum receivers 507, 509 further
validate the serial transmitter message and forward this
information to computer 508 for display.

15 The spread spectrum of the present invention, in a preferred
embodiment, uses fast frequency shift keying (FFSK). The
techniques disclosed below are equally applicable for frequency
hopping or phase shift keyed spread spectrum methods.

Transmitter

20 Referring to Fig. 2, a preferred embodiment of the
transmitter of the instant invention is shown including
chip-code-generation means, preamble means, address means, data
means, timing means, pseudorandom-sequence means, and
error-detection means. The chip-code-generation means may be

embodied as a recirculating register 10 and the preamble means may be embodied as a preamble register 11. The chip-code-generation means may be embodied as a shift register with exclusive ORed feedback taps. The address means may be embodied as an address register 14, the data means may be embodied as a data register 18, and the error-detection means may be embodied as cyclical-redundancy-check (CRC) generator 19. The timing means may be embodied as timing circuit 13, and the pseudorandom sequence means may be embodied as the random number generator 17.

In the exemplary arrangement shown, a microprocessor 8 includes the recirculating register 10, preamble register 11, address register 14, data register 18, CRC generator 19, random number generator 17, and timing circuit 13. The timing circuit 13 is embodied as a timing algorithm in software, located in microprocessor 8. Alternatively, these registers and circuits may be put together with discrete components or independently wired and constructed as separate elements, as is well known in the art.

As shown in Fig. 2, an oscillator, which is shown as a voltage controlled oscillator 2 is coupled to an RF power amplifier 3, and the RF power amplifier 3 is coupled through a bandpass filter 4 to a micropatch⁴ antenna 5. The voltage controlled oscillator 2 includes an enable input and a modulation

00055370 052007

5 input, where the voltage controlled oscillator generates a spread spectrum signal in response to a modulating voltage being applied to the modulation input. The voltage controlled oscillator 2 is enabled by applying an enable signal to the enable input. The RF power amplifier 3 has a keying input and will amplify a signal from the voltage controlled oscillator 2 only if a keying signal is applied to the keying input. The voltage controlled oscillator 2 alternatively can be frequency locked to the microprocessor's crystal to improve stability. The voltage controlled oscillator 2 also can be replaced by a capacitor and inductor tuned oscillator and a phase shift keyed modulator, or any other means for generating a signal. *

10

15 The microprocessor 8 is coupled to the modulation input of the voltage controlled oscillator 2 through first resistor R6 and second resistor R7. The microprocessor 8 broadly controls the voltage controlled oscillator 2 by supplying an enable signal to the enable input of the voltage controlled oscillator 2, and a modulating voltage to the modulation input of the voltage controlled oscillator 2. Also, the microprocessor 8 controls the RF power amplifier 3 by supplying a keying signal to the keying input of the RF power amplifier 3.

20 Included in the microprocessor 8 is a recirculating register 10 coupled to the modulation input of the voltage controlled oscillator 2 through second resistor R7. The recirculating

register 10 stores a spread spectrum chip code, and outputs, during a transmitting interval, the spread spectrum chip code as a modulating voltage to the modulation input of voltage controlled oscillator 2.

5 The preamble register 11 is coupled to the modulation input of the voltage controlled oscillator 2 through first resistor R6. The preamble includes the coarse lock preamble and the ~~fine~~ ^{PR} fine lock preamble. The preamble register 11 stores a coarse lock preamble in cells 12 and a fine lock preamble in cells 24.

10 The preamble register 11 outputs during the transmitting interval, the coarse lock preamble and the fine lock preamble as a modulating voltage to the modulation input of the voltage controlled oscillator 2 through first resistor R6. First resistor R6 and second resistor R7 are chosen such that the
15 desired spreading from the chip code and the data coming from the preamble register 11 is achieved.

Also shown in Fig. 2 is an address register 14 coupled to the modulation input of the voltage controlled oscillator 2 through the preamble register 11 and first resistor R6. The
20 address register 14 stores a device address and a type code, and outputs during a transmitting interval, the device address and type code as a modulating voltage to the modulation input of the voltage controlled oscillator 2.

A data register 18 is coupled to a data input 20 and to the

modulation input of the voltage controlled oscillator 2 through the preamble register 14 and the address register 11. The data register 18 stores data received from the data input, and outputs, during the transmitting interval, the data as a modulating voltage to the modulation input of the voltage controlled oscillator 2. The data from the preamble register 11, address register 14, and data register 18 are outputted in sequence, and at the end of a sequence, the cyclical redundancy check generator 19 outputs a data word at the end of the code for error detection.

A timing circuit 13 is included in microprocessor 8, and is coupled to the enable input of the voltage controlled oscillator 2 and to the keying input of the RF power amplifier 3 for enabling the voltage controlled oscillator 2 and the RF power amplifier 3, by outputting an enable signal to the enable input and a keying signal to the keying input of the RF power amplifier 3, respectively, during the transmitting interval. In essence, voltage controlled oscillator 2 and RF power amplifier 3 are not active or activated during a time duration of non-transmission, and are only activate during a transmission interval. The time duration between transmission intervals is made to vary in response to the random number generator 17 generating a random number and transferring the random number to the timing circuit 13. The random number modifies the timing duration between each

transmitting interval randomly. ~~Alternatively, an algorithm based on the address of the facility having the spread spectrum transmitter, can be used with the facility address as the kernel for making the time between transmissions random.~~

Also shown are the voltage supply, regulator circuit 1, and battery low detector 25.

The spread spectrum transmitter monitors one or more data inputs 20 and transmits periodically a supervisory data message. One or more of the data inputs 20 can be set 21 such that they cause a priority transmission at an increased rate higher than the supervisory message rate.

During installation of the transmitter, a device address (1-4095) 12, "Type" code 15 (fire, security, panic, heat, pull station, etc.) stored in preamble register 11, and a spread spectrum chip code stored in recirculating register 10 are loaded via programming connector 16. At installation time the "Panel" computer assigns the device ID address to each room number or unique device in the system which is to be monitored. The panel computer then prints a sticky label with the device's ID, address, type code and spread spectrum chip code, both in decimal and bar code form. The label is fixed to the smoke detector or alarming device and via the programming connector 16, or the number can be entered manually with the aid of a hand-held terminal. Alternatively a bar code reader can be connected to

the programming connector 16 and the device can be read electronically from the bar code and entered into the transmitter. Microprocessor timing is controlled by crystal 23.

Transmit timing is controlled by the wake-up timer 9, which has its own low power oscillator.

In operation, the transmitter sends a supervisory message often enough so that the receiver can detect failure of any transmitter within 200 seconds. The microprocessor 8 effectively "sleeps" between these transmissions to conserve battery life while counter 9 counts down to wake-up microprocessor 8. In order to minimize the chance of reoccurring data collisions from multiple simultaneous transmitters, the transmit interval is modified by random number generator 17. Very fine resolution intervals are used equal to ^{12.5} 500 temporal transmit positions. The random number generator 17 is seeded with the transmitter's unique address 14, resulting in different transmit schedules for each unit, thereby avoiding continuous collisions between transmitters.

Once the microprocessor 8 is reset by the wake-up circuit 9 the timing circuit 13 allows the crystal 23 to stabilize for 1-5 ms. The timing circuit 13 then enables the transmitter oscillator 2 and allows it to stabilize for 1 ms. The timing circuit 13 subsequently enables the RF amplifier 3 by sending a

keying signal to the keying input. The RF energy from the RF amplifier 3 is filtered by bandpass filter 4 to reduce spurious RF emissions. The filtered signal is passed to a PCB foil micropatch 2 dBi gain antenna 5 which radiates the RF energy to an appropriate receiver. When the timing circuit 13 keys the RF power amplifier 3 it also begins to recirculate the spread spectrum 31 chip code stored in recirculating register 10 at a chip rate of 1 to 1.3 MHz. The chip code in turn causes a voltage swing 0-5 volts at the modulation input of the microprocessor. The voltage swing in conjunction with a modulation setting second resistor R7 creates a proportional current which modulates voltage controlled oscillator 2 thereby generating a spread spectrum FSK signal. ~~The modulator index of 90° causes the FSK signal to occupy an RF bandwidth of only 1.3~~ ~~chip rate.~~ This improves the signal to noise ratio at the receiver by reducing required bandwidth and minimizes the chances for intersecting interference. The data is super imposed on the chip code by the resistor 6 as a 1/31 deviation of the total modulation. Two or three adjacent chip code sequences are used to equal one bit time resulting in a baud rate of 14-21 KB/s.

In order for a receiver to demodulate a spread spectrum chip code, it must time lock onto the spread spectrum chip code. Disclosed are three methods of this timing acquisition, one is serial and two are parallel assisted. All methods require some

00559376 "052097
synchronization bits in the transmitted message specifically
allocated to code timing acquisition, which allow the receiver to
search the code and find a correlation peak. The serial
correlator searches one bit time per chip in the code sequence to
5 achieve a $\pm 1/2$ chip code lock. This search can be hastened by
searching one code sequence time instead of one bit time thereby
providing a two or three to one speed increase. The parallel
correlator searches all 31 chip sequences in parallel so that an
initial $\pm 1/2$ chip synchronization ("lock") can be achieved in one
10 bit or one chip code sequence time. "Fine" code lock ($\pm 1/4$ chip)
for either serial or parallel assisted schemes must be followed
by transmitted bit times allocated to allowing the receiver to
achieve a higher resolution correlation "time" lock. One quarter
chip lock accuracies perform to within ~~1.5 dB~~ ^{1.25 dB} of optimal code
15 alignment. The receiver's fine code lock algorithm seeks to
optimize the correlation peak. Higher levels of code lock can be
achieved by searching in smaller fractions of a chip. This can
facilitate "time of flight" distance or location measurement
applications such that 25 ns, 25 feet, of measurement resolution
20 can be achieved.

The transmitter's microprocessor 8 stores a synchronizing
preamble in preamble register 11 of 36 bits for a serial
correlator, which are broken into 31 bits for coarse lock 11 and
5 bits for fine lock 12. For the two parallel correlation

Receiver

The spread spectrum receiver comprises several major blocks:

- A. The RF section which converts the received signal to lower frequencies;
- B. Chip code generator with means of chip code phase shifting for correlation lock;
- C. Means to measure both signal strength and quieting to detect correlation lock over the dynamic range of the system;
- D. An adaptive data demodulator tolerant to DC i.e.: long strings of 1's or 0's; and
- E. microprocessor algorithms to perform the above.

Fig. 3A shows the RF portion of the receiver which converts the received signal to lower frequencies. Fig. 3B shows a chip code generator with means for shifting a chip code phase for correlation lock, and means for measuring signal strength and the quieting output of the receiver to detect correlation lock over the dynamic range of the system. In Fig. 3A, a first polar diversity antenna 100 and a second polar diversity antenna 102 are shown and are physically turned so that their spatial phase relationship is 90° . Signals received from each of the first and second polar diversity antennas 100, 102 are passed through a 45° phase shifting network 104, 103, respectively and then to a

22

combiner 105. The combiner 105 combines the signals received from the first and second polar diversity antennas 100, 102. The combined signal then passes through a first bandpass filter 106, is amplified by amplifier 107 and passed through a second
5 bandpass filter 108, and is mixed with the mixer 109. Typically, a crystal 125 controls the frequency of an oscillator 126. The signal from oscillator 126 is frequency multiplied by first, second and third frequency multipliers 128, 129, 130. The signal is mixed at first mixer 109 with the received signal from second
10 bandpass filter 108. The oscillator 126 ^{IS MODULATED BY A PR} receives the spread spectrum chip code through a phase shifter 127. The spread spectrum chip code is generated by the circuit in Fig. 3B. First mixer 109 down converts the received signal to a first
intermediate frequency signal. The first intermediate frequency
15 signal is in a first intermediate frequency range, and is passed through third bandpass filter 110, amplified by second amplifier 111 and passed through fourth bandpass filter 112. The output signal from bandpass filter 112 is mixed with a second mixer 113 with a second oscillator signal from second oscillator 132 to a
20 second intermediate frequency. The frequency of the second oscillator 132 is controlled by second crystal 131 and frequency multiplied by fourth frequency multiplier 133. The second intermediate frequency signal is then passed through fifth bandpass filter 114, amplified by third amplifier 115, filtered

by sixth bandpass filter 116, and amplified by fourth amplifier 117. The second intermediate signal then passes via two routes. The first route passes through seventh bandpass filter 118, fifth amplifier 119 and quadrature detector 121. The quadrature detector 121 is coupled to a 90° phase shift network 120. The output of the quadrature detector 121 is the pre-data. Taps are taken from fourth and fifth amplifiers 117, 119. Signals from these taps pass through signal strength combiner 122, pass through eighth bandpass filter 123 and sixth amplifier 124. The output of sixth amplifier 124 is the signal strength.

Referring to Fig. 3B, an apparatus which is embodied as a microprocessor 147 is shown for synchronizing a spread spectrum chip code using a two step algorithm in a microprocessor coupled to the pre-data output of the receiver. The signal from the pre-data output of the receiver passes through circuitry for generating a quieting output of the receiver.

The signal from circuitry coupled to the pre-data output, for generating the quieting output, includes amplifier 135, ninth bandpass filter 140, signal compressor 141, quadrature detector filter 142 to produce the quieting output from seventh amplifier 143. The output of seventh amplifier 143 is the quieting output, and passes to the microprocessor 147 through analog to digital converter 150. The pre-data signal also passes through a filter comprising fourth and fifth resistors 138, 137 operational

amplifier 139 with sixth resistor 158, and first and second capacitors 157, 156. This signal is fed to the microprocessor 147.

5 The microprocessor 147 further includes means coupled to the correlation means for computing the adaptive average in response to the amplitude of the first data signal not exceeding the preset margin by adding the amplitude of the first data signal to the previously computed adaptive average. The microprocessor 147 comprises means coupled to the quieting output of the receiver 10 via amplifier 143 for correlating the amplitude of a second data signal in response to the amplitude of the first data signal exceeding the preset margin. The second data signal is from the quieting output of the receiver. The first data signal is the digitized amplitude of the first signal, and the second data signal is the digitized amplitude of the second signal. When correlating the second data signal, the microprocessor 147 compares ~~a portion of one chip~~ ^{multiple iterations of} the spread spectrum chip code, by comparing the second data signal to the adaptive average by a preset margin to determine whether the amplitude of the second data signal exceeds the preset margin. 15 20

The microprocessor 147 synchronizes the spread spectrum chip code by comparing the first signal during one information bit to an adaptive average to determine whether coarse correlation has been achieved. In response to the first signal not achieving

0055370 0550097
coarse correlation, the microprocessor 147 computes an adaptive
average by adding a first portion of the first data signal to a
second portion of the adaptive average. Additionally, the
microprocessor 147 correlates a second signal in response to the
amplitude of the first signal exceeding the ~~quieting output of~~ ^{to a chip} ~~the receiver~~ ^{adaptive average by a preset margin} within a portion of one chip of the spread spectrum
chip code by comparing the amplitude of the second signal to the
adaptive by a preset margin to determine whether the second
signal exceeds the preset margin.

10 The microprocessor 147 also generates a spread spectrum chip
code for use with the receiver, which is inputted through phase
shifter 127 to oscillator 126 of Fig. 3A. The apparatus, which
includes the microprocessor 147 and related circuitry, includes
means for entering a spread spectrum chip code having n chips.
15 The entering means may be embodied as hand terminal 153. Also,
the apparatus includes memory means for storing chip words, which
may be embodied as random access memory 146. The random access
memory 146 is coupled to the microprocessor 147. The random
access memory 146 stores each chip word having a plurality of
20 bits per chip. In a preferred embodiment, there are four bits
per chip word. The apparatus further includes counting means
coupled to the random access memory 146 for sequencing through n
addresses of the chip words in the random access memory 146 and
sequentially outputting the chip words to the receiver. The

with the clock input 156 sets this chip code rate. The binary counter 144 causes the RAM 146 to sequentially select and modulo repeat the entire stored chip code. The AND gate ¹⁵⁹159 determines the 31st count state $\times 4$ to create a reset pulse and causes the counter to cycle through (31×4) modulo states. In order to rapidly jump to any chip code table position the summer 145 is used to add offset 161 selected by the microprocessor's search algorithm. The flip-flop 160 synchronizes the output of the RAM 146 to the chip code clock 156 to avoid variable propagation delays due to the counters and adders.

Once the chip code has modulated the oscillator 126, ~~by 128~~⁵, the combined signal is multiplied by 128, 129, and 130 to provide a signal from the first local oscillator to frequency mixer 109. This mixing stage 109 provides several features including lowering the frequency to 160 MHz, narrowing the bandwidth to 125 kHz, and when the microprocessor locks the code sequence, the mixer 109 despreads the original transmitted data signal.

The first mixer 109 output is bandpass filtered by third bandpass filter 110, amplified by second amplifier 111 and bandpass filtered by fourth bandpass filter 112. The first intermediate frequency signal is mixed by second mixer 13 with a signal from the second local oscillator. The second local oscillator signal originates from second oscillator 132 and is controlled by crystal 131. The resulting sine wave is frequency

00059378-052097

multiplied by fourth frequency multiplier 133 before being mixed at second mixer 113. The signal resulting from the second mixer 113 is lowered in frequency to 10.7 MHz and is bandpass filtered by fifth bandpass filter 114, amplified by third amplifier 115 and bandpass filtered by sixth bandpass filter 116. This signal is sent to fourth amplifier 117 with feedback bias current measured along with fifth amplifier 119 by a signal strength measurement circuit 122. The signal strength measurement is low pass filtered by first lowpass filter 123 and buffered by sixth amplifier 124 before passing to the signal strength analog multiplexer input 152.

The signal from fourth amplifier 117 is filtered by sixth bandpass filter 118 and amplified by fifth amplifier 119. This output of fifth amplifier 119 is then quadrature detected with the aid of phase shifting circuit 120. The output of the quadrature detector 121 is buffered by amplifier 135, then high pass filtered 140. The signal is compressed to a manageable 45 dB dynamic range by compressor 141. The compressed signal is passed through a quieting detector filter 142 and buffered by amplifier 143 before being inputted to the analog multiplexer input 151.

The "pre-data", buffered by amplifier 135, is also presented to an adaptive data demodulator. Varying DC levels will be present on this signal due to frequency uncertainty between the

receiver and transmitters. The data 1/0 decision threshold is chosen as the average voltage of an alternating 1/0/1... pattern in the synch preamble. During the preamble code lock search time, the analog switch 136 is enabled and pre charges capacitor 156 through resistor 137. This places an average voltage on capacitor 156 between a logic "1" and a logic "0". Once code lock is achieved, and the data message synchronization bit 24 is detected, the analog switch 136 is opened leaving the capacitor 156 at a stable level for the duration of the message. The buffered pre-data level is then filtered 157 with hysteresis set by resistors 158 and 138 and compared to the voltage level on capacitor 156. This results in reliable data bits provided on the output of voltage comparator 139.

Code Locking Algorithm

The code locking algorithm seeks to determine a correlation peak by comparing the received RF signal energy to a microprocessor controlled copy of the desired chip code pattern. The code locking algorithm digitizes the quieting detectors analog output once per bit time. The software maintains an adaptive average of the quieting samples to determine the level of correlation improvement. The described algorithm code locks to within 1/4 chip time or within 1.25 dB of optimum. The ~~signal strength or~~ ^{→ A R} baseband output also can be used in place of the

quieting output.

5 The present invention includes three methods of using a
microprocessor for synchronizing the timing acquisition of a
spread spectrum chip code received by the receiver. The spread
10 spectrum signal comprises a plurality of information bits. Each
information bit is spread in spectrum by a plurality of chips
from a spread spectrum code. The first method, as depicted in
Fig. 4, comprises the steps performed by the microprocessor of
inserting 401 a delay of one information bit time before the
15 first information bit received by the receiver, and sampling and
digitizing 402 the first signal from the quieting output of the
receiver to generate a first data signal. The sampling and
digitizing alternatively can be taken from the baseband or signal
strength output of the receiver. The first method compares 404
20 the amplitude of the first data signal to the adaptive average
during the time of one information bit to determine whether
coarse correlation has been achieved. In response to coarse
correlation not being achieved, the method computes 405 the
adaptive average by adding a first portion of the amplitude of
the first data signal to a second portion of the previously
computed adaptive average. If the coarse correlation has been
achieved, then the method shifts 407 the chip code by a third
portion of one information bit time. In a preferred embodiment
of the present invention, the chip time is divided into four

If coarse correlation is achieved 404, then the algorithm seeks to "fine" code lock. The chip code phase shifter 161 is shifted 407 by one ($1/4$ chip time). The one information bit time synchronizing delay is passed 408. The quieting detector output is digitized 409 and compared 410 to the running quieting output average. If the new sample did not improve 411 the quieting by the preset margin then the chip code phase shifter is incremented 412 by $1/4$ chip to its past more optimum position. Fine lock is completed 414 and the code lock algorithm jumps to a data capture algorithm.

If the required margin of quieting improvement is achieved 411, then the number of chip code shifts is checked 413. Any search code position which is shifted more than three $1/4$ chip steps would undesirably slip one whole code cycle. Comparison 413 stops a search on the third-code slip and assumes an optimum correlation is achieved then proceeds to the data acquisition algorithm 414. If three code phase decrements have not occurred, the algorithm repeats at shift 407.

Fig. 5 shows four cases with one-quarter chip code lock achieved in each case using the first method.

A second method and apparatus for synchronizing a spread spectrum chip code using the baseband signal output of the receiver is shown in Fig. 6. The apparatus aspect of the invention includes means for sampling and digitizing a plurality

of analog baseband signals, register means for shifting the plurality of data signals, means for adding in parallel the plurality of data signals, means for comparing the correlation sum and means for dithering a chip/sample clock by a portion of a chip time. The sampling and digitizing means may be embodied as analog to digital converter 201. The register means may be embodied as the plurality of registers 202, 203, 204. The adding means may be embodied as adders 205, 206, 207 and the comparing means may be embodied as comparator 213. The dithering means may be embodied as the microprocessor 215.

As illustratively shown, the apparatus for synchronizing the spread spectrum chip code has the analog to digital converter 201 coupled to the RF baseband output of the receiver 212. The analog to digital converter 201 samples and digitizes the plurality of analog baseband signals from the baseband output of the receiver 212 and generates a plurality of data signals. The plurality of registers 202, 203, 204 is coupled to the analog to digital converter 201 and shifts the plurality of data signals sequentially through the plurality of registers 202, 203, 204. The plurality of adders 205, 206, 207 are coupled to the plurality of registers 202, 203, 204, respectively, for adding in parallel each of the data signals stored in the plurality of registers 202, 203, 204 according to a plurality of predetermined weights for each of the plurality of data signals, respectively,

to generate a correlation sum. The weights are controlled by flip flop circuits 209, 210, 211, which contain the spread spectrum chip code. The adder 207 outputs a correlation sum 208 to a comparator 213 for comparing the correlation sum to a predetermined margin or threshold. The dithering circuit embodies as a microprocessor 215 is coupled to the comparator 213 and dithers the chip clock by at least a first portion of one chip time, thereby improving chip lock.

In operation, the second method of using a microprocessor for synchronizing the timing acquisition of the spread spectrum chip code received by a receiver comprises the steps of sampling and digitizing using the analog to digital converter 201, the plurality of analog baseband signals from the baseband output of the receiver 212, to generate a plurality of data signals. Each of the analog baseband signals is sampled and digitized during one chip time. The method shifts the plurality of baseband signals through the plurality of shift registers 202, 203, 204. The plurality of data signals are added in parallel according to a plurality of predetermined weights, from flip flops 209, 210, 211 for each of the plurality of data signals, respectively, in the plurality of adders 205, 206, 207 to generate a correlation sum 208. The correlation sum 208 is compared to a predetermined threshold or preset margin, and a chip clock is then dithered by at least a first portion of one chip time to improve clock lock.

In a preferred embodiment, the first portion is one quarter of one chip time.

5 The chip clock samples once per chip time. A coarse chip lock may therefore be incorrect by $\pm 1/2$ of a chip. To improve the lock, the chip clock is slewed in $\pm 1/4$ and/or $\pm 1/8$ chip steps controlled by an algorithm in microprocessor 215. A clock with a rate equal to four times the chip rate is counted by counter 214. The counters output is compared to an output of the microprocessor 215 equal to the code phase being searched. The microprocessor 215 can thereby search in fine chip code steps after a rapid parallel assisted search in 1, 31 chip code time. The total search required is equal to 6 chip code times, which can be sent in the spread spectrum transmitters code-lock preamble as disclosed.

10 15 As a further component reduction of the circuitry described above in the second species of the method and apparatus for synchronizing a spread spectrum chip code, the parallel assisted chip code lock can be serially summed instead of parallel summed. The serial sum of all 31 stages must be computed between chip samples (less than 1,000 ns). This speed can be achieved with available high speed CMOS ASICS with clock speeds of 40 MHz or greater.

20 A third species of the spread spectrum chip code synchronizing method and apparatus is disclosed in the present

invention, and is set forth in Fig. 7. The third species of the spread spectrum chip code synchronizing apparatus couples to the baseband output of the receiver. The apparatus includes means coupled to the baseband output of the receiver for sampling and digitizing the plurality of analog baseband signals, register means coupled to the sampling and digitizing means for shifting and recirculating the plurality of data signals, and means coupled to the register means for adding sequentially the data signals passing through the shift register means. As shown in Fig. 7, the sampling and digitizing may be embodied as analog to digital converter 310. The register means may be embodied as registers 307, 308, 309 and the adding means may be embodied as adder 303. As shown in Fig. 7, the analog to digital converter 310 is coupled to the baseband output of the receiver, and passes through a plurality of gates 302 to the plurality of registers 307, 308, 309, to adder 303. Also shown is a plurality of flip flops 306, 311, 312 having the spread spectrum chip code therein. The flip flops 306, 311, 312 input the spread spectrum chip code into the adder 303. The adder 330 is coupled to a correlation sum accumulator 304 which outputs a correlation sum 305.

In the preferred embodiment, the third species of the apparatus for synchronizing the spread spectrum chip code has the analog to digital converter 310 coupled to the baseband output of

the receiver for sampling and digitizing a plurality of analog baseband signals and generating a plurality of data signals. Each of the analog baseband signals is sampled and digitized during one chip time. The plurality of registers 307, 308, 309 is coupled to the analog to digital converter 310 through gates 302 for shifting and recirculating the plurality of data signals sequentially through the plurality of registers 307, 308, 309 and gates 302. The adder 303 is coupled to register 309 for adding sequentially the data signals passing through registers 309 according to predetermined weights set forth in flip flops 306, 311, 312.

In operation, the third method of uses a microprocessor for synchronizing the timing acquisition of the spread spectrum chip code received by the receiver. The method samples and digitizes the plurality of analog baseband signals from the baseband output of the receiver using analog to digital converter 310, to generate a plurality of data signals. Each of the analog baseband signals is sampled and digitized during one chip time. The method further includes shifting and recirculating the plurality of data signals sequentially through the plurality of registers 307, 308, 309. The data signals are added sequentially as they pass through register 309 using adder 310 and accumulated. The correlation sum accumulator 304 then passes the correlation sum 305 to the microprocessor.

of the Ain inputs. The outputs of accumulator 304 are transferred to the next register stage and then at the next clock rising edge, the accumulator stores that total. After 31 summing clock cycles the accumulation 304 will contain the correlation sum 305. The multibit words stored and summed by the two alternative methods can be reduced to one bit samples and sums, resulting in a small loss of performance.

It will be apparent to those skilled in the art that various modifications can be made to the wireless detection system of the instant invention without departing from the spirit or scope of the invention, and it is intended that the present invention cover modifications and variations of the wireless detection system provided they come within the scope of the appended claims and their equivalents.